




Product Descriptions

No.	Name	Picture	Parameters	Remarks
1	Coffee beans elevator (suction conveyor)		<p>Motor:0.75kw Conveying capacity :350kg/h Conveying height :4.5m Material hopper volume :12L Conveying tube calibre:38mm External Dimensions:400*300*500mm Weight :25kg</p> <p>The small working platform can move . It can move from left to right automatically Convenient to check silo</p>	
2	Single head liner weigher for the whole beans measuring		<p>Measuring range:10g-2kg Accuracy:0.2g-2g Speed:5--30bags per min Hopper volume:3L Control system:PLC Touch screen:7 inch Voltage :AC220V ±10% 50Hz(60Hz)</p>	
2.1	Working platform		304stainless steel,equip with truckle	

3

Doy bagger :
Model:DB430
High level version



Technical data:

1. bag material: Multilayer Composite Premade Bag (e.g.: PET/PE)
2. bag format: three side sealing bag、standup pouch
3. Upgradable Bag Type: Gusset Bag, Zipper Bag, Flat Bottom Pouch (Need additional purchase of functional device)
4. bag size: $80\text{mm} \leq W \leq 300\text{mm}$
 $100\text{mm} \leq L \leq 430\text{mm}$
5. Speed: 0--15bags per min
6. voltage: 220V, single phase, 50/60HZ, 1.2KW
7. bleed pressure: 0.65Mpa
8. air consumption: $0.3\text{m}^3/\text{min}$ (standard machine, excluded extra function)
9. machine body size: 1770*510*1360mm
10. machine packaged size: 1860*600*1650mm (Export non-fumigation wooden case)

Basic configuration:

1. PLC: Japan Panasonic
2. Touch screen: China Kinco 7 inches color touch screen;
3. cylinder: Taiwan Airtac
4. Vacuum Generator: China Airbest
5. Vacuum Component: Japan SMC;
6. vacuum manometer: Japan SMC
7. PID temperature control: Japan Omron
8. Electrical Component: Schneider / Omron

Basic Functions:

1. The machine stops running when the safety key interlock switch is pulled out;
2. No bag prompting function;
3. Self-diagnosis function of open the bag failed (The bag can be reused); In that case, the machine will not fill and seal, it will re-take the bag;

Performance Features:

1. Easy to operate and easy to replace the bag / The machine is suitable for a variety of bag types;
2. Low maintenance cost / Modular replacement of the parts;

			3. CE Certificate of Conformity.	
4	Z type output conveyor			
5	Turn table		<p>1.Main frame is to be SUS304</p> <p>2.Table diameter :Φ1200*2</p> <p>3.Height:750mm</p> <p>4.Control panel ,can adjust speed</p> <p>5.Power :0.55KW</p> <p>6.Single phase/three phase 220V/380V;50HZ/60HZ</p>	
6	Beans container with weighing function		customized	